


OVERVIEW



1. Thunderbolt 4	5. USB 2.0
2. USB 3.2 Gen 1 (Always On)	6. Ethernet (RJ-45)
3. HDMI 1.4b	7. Kensington Security Slot
4. Headphone / microphone combo jack (3.5mm)	

PERFORMANCE

Processor

Processor Family

11th Generation Intel® Core™ i3 / i5 / i7 Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i3-1115G4	2	4	3.0GHz	4.1GHz	6MB	DDR4-3200	Intel UHD Graphics
Core i5-1135G7	4	8	2.4GHz	4.2GHz	8MB	DDR4-3200	Intel Iris® Xe Graphics
Core i7-1165G7	4	8	2.8GHz	4.7GHz	12MB	DDR4-3200	Intel Iris Xe Graphics

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Pro 64
- No operating system

Graphics

Graphics^[1]

Graphics	Type	Memory	Key Features
Intel UHD Graphics	Integrated	Shared	DirectX® 12
NVIDIA® GeForce® MX350	Discrete	2GB GDDR5	DirectX 12
NVIDIA GeForce MX450	Discrete	2GB GDDR5	DirectX 12
Intel Iris Xe Graphics	Integrated	Shared	DirectX 12

Notes:

1. The integrated graphics of i5 / i7 models is Intel Iris Xe Graphics but function as Intel UHD graphics due to single channel memory limitation

Monitor Support

Monitor Support

Supports up to 3 independent displays via native display and 2 external monitors; supports external monitors via HDMI® (up to 4096x2160@30Hz) or Thunderbolt™ (up to 5120x3200@60Hz)

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Memory Type

DDR4-3200

Memory Slots

One DDR4 SO-DIMM slot

Max Memory^[1]

Up to 32GB DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

Up to two drives, 1x M.2 2242 SSD + 1x M.2 2280 SSD

- M.2 2280 SSD up to 1TB
- M.2 2242 SSD up to 512GB

Storage Type^[1]

Disk Type	Interface	RPM	Security
M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x4	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	Opal2

Notes:

1. M.2 2280 slot supports PCIe 4.0 x 4

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™, HARMAN-branded

Microphone

Dual array microphone

Camera

- 720p, with privacy shutter, fixed focus
- IR & 720p, with privacy shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life^[1]

MobileMark® 2014: 11.9 hr

MobileMark 2018: 8.7 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

65W USB-C AC adapter

DESIGN

Display

Display^[2]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
14.0"	FHD (1920x1080)	Multi-touch	IPS	300 nits	Anti-glare	16:9	800:1	45% NTSC	170°	-

14.0"	FHD (1920x1080)	None	IPS	250 nits	Anti-glare	16:9	800:1	45% NTSC	170°	-
14.0"	FHD (1920x1080)	None	TN	220 nits	Anti-glare	16:9	500:1	45% NTSC	90°	-
14.0"	FHD (1920x1080)	None	IPS	300 nits	Anti-glare	16:9	1200:1	100% sRGB	170°	-

Touchscreen

- Capacitive-type on-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>
2. Displays with 300nits brightness (multi-touch and non-touch) are NOT available in EMEA

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

- LED backlight
- Not support

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)

Models	Dimensions
Aluminium (top), aluminium (bottom) models	324 x 220 x 17.9 mm (12.76 x 8.66 x 0.7 inches)
Aluminium (top), PC + ABS (bottom) models	324 x 220 x 18.9 mm (12.76 x 8.66 x 0.74 inches)
PC + ABS (top), PC + ABS (bottom) models	324 x 220 x 19.9 mm (12.76 x 8.66 x 0.78 inches)

Weight

Models	Weight
Aluminium (Top), PC + ABS (Bottom) models	1.59 kg (3.51 lbs)
PC + ABS (Top), PC + ABS (Bottom) models	1.69 kg (3.73 lbs)
Aluminium (Top), Aluminium (Bottom) models	1.64 kg (3.62 lbs)

Case Color

- Black
- Mineral metallic

Case Material

- Aluminium (top), aluminium (bottom)
- Aluminium (top), PC + ABS (bottom)
- PC + ABS (top), PC + ABS (bottom)

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, Realtek RTL8111H-CG

WLAN + Bluetooth™^[1]

- Intel Wireless-AC 9560, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card

WWAN

Not Support

SIM Card

No SIM card

NFC

Not support

Notes:

1. Intel WiFi 6 full features might be limited by country level restrictions
Bluetooth 5.2 is supported with driver version 22.30 and later

Ports^[1]**Standard Ports^[2]**

- 1x USB 3.2 Gen 1 (Always On)
- 1x USB 2.0
- 1x Thunderbolt 4 / USB4™ 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI 1.4b
- 1x Ethernet (RJ-45)
- 1x headphone / microphone combo jack (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

SECURITY & PRIVACY

Security

Security Chip

- Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset

Physical Locks

Kensington® Security Slot

Smart Card Reader

No smart card reader

Fingerprint Reader

- Touch style fingerprint reader on power button
- No fingerprint reader

BIOS Security

- Power-on password
- Supervisor password
- Hard disk password
- Self-healing BIOS

Other Security

- Camera privacy shutter
- (Optional) IR camera for Windows Hello

SERVICE

Warranty

Base Warranty

- 1-year mail-in service
- 1-year depot service
- 1-year limited onsite service
- 1-year depot with 2-year system board service
- No base warranty

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Operating: 5°C to 35°C (41°F to 95°F)
- Storage and transportation in original shipping package: -20°C to 60°C (-4°F to 140°F)
- Storage without package: 5°C to 43°C (41°F to 109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- ErP Lot 3
- TCO
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

TUV Low Blue Light certified

