Akuvox C313W

Datasheet

Premium touch screen for your home

The Akuvox C313W multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.

At a Glance

- Ultra—clear, stylish appearance;
- Thin profile and small footprint;
- 7—inch capacitive touch screen with energy saving mode;
- Two-way audio communication with other units in the network;
- · Complies with SIP standard for easy integration in every SIP capable PBXes;
- Powered by PoE or external source
- Support US or European electrical wall box mounting

Physical & Power

- Front panel: Plastic
- RAM / ROM: 128MB / 128MB
- Display: 7 Inch TFT LCD
- Screen: 7 Inch capacitive touch screen
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz
- RS485 port: Support
- Relay out: 1
- Bell in: 1
- I/O: 8

- Microphone: -58dB
- Speaker : 4 Ω / 2 W
- Ethernet ports: 2xRJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- 12V DC connector (if not using PoE)
- Installation: Wall-mounted & Desktop
- Dimension: 200.2x132.2x27.2mm
- Working Humidity: 10~90%
- Working Temperature: -10° C $^{\sim}$ $+45^{\circ}$ C
- Storage Temperature : -20° C $^{\sim}$ $+70^{\circ}$ C



10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com Constraints of the second seco

Akuvox C313W

Datasheet

Touch Screen Display

- Display Mode: Normally white, Transmissive
- LCD Size: 7inch (Diagonal)
- Resolution : 800x480
- Contrast ratio: 500:1
- Luminance: 220 cd/m²
- Viewing Angle: 50° Left, 50° Right,

40° Upper, 50° Lower

• Touch Screen: Projected capacitive

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711 µ, G.729 Application Scenario
- Broadband audio codec: G.722
- DTMF: Out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation

Video

• Streaming formats: H.264

Networking

• Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Firmware upgrade
- System logs (include door access logs)
- Villas
- Apartment complexes
- Home automation systems
- Modern interiors



10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com Akuvox_190917_V2.