Akuvox R20K-2

Perfect Doorphone choice for daily life

2-wire video intercom systems remain demanded as long as there are so many houses left with old wiring in the walls, which is indeed problematic to replace. Akuvox came up with a solution to address the issue to allow you to get the benefits of IP networktype system, but with old wiring and with no replacements done

At a Glance

- Two-pin wire for power supply and network access
- Wide-angle camera: 110° (H), 58° (V);
- IC/ID Card Reader & Keypad embedded;
- Two-way audio communication over IP networks with Echo Cancellation & Noise suppression;
- H.264 video compression;

Physical & Power

- Front panel: Aluminum alloy
- Camera: 2M pixels, automatic lighting
- Keypad: Yes
- Light sensor: Support
- Infrared sensor: Support
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz (with NFC) & 125kHz
- Relays out: 1
- Inputs: 1

- Microphone: 1
- Speaker: 1
- Power Interface: 1
- Power supply: 48VDC / 24VDC
- Water-proof & Dust-proof: IP65
- Installation: Flush-mounted or Wall-mounted
- Flush-mounted DIM: 226x108x52mm
- Wall-mounted DIM: 185x85x29mm
- Working Humidity: 10~90%
- Working Temperature: $-30^{\circ}C \sim +60^{\circ}C$
- Storage Temperature: -40°C ~ +70°C

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com



Datasheet

Akuvox R20K-2

Datasheet

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- \bullet Narrowband audio codec: G.711a, G.711 μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.7", CMOS
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p 25fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

 Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control



10/F, No.56 Guanri Road, Software Park II -, Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com Akuvox_202303_V2.0