

### Technical caracteristics

Main power supply	220-230 Vac 50/60 Hz					
Motor voltage	24Vdc					
Maximum power consumption	300 W					
Control board	Control Board Levixo 40/60					
Obstacle detection	Encoder					
Opening time	2,5 s to 6 s (Levixo 40) / 3 s to 9 s (Levixo 60)					
	4 m without accessories (Levixo 40) / 6 m without accessories (Levixo 60)					
Boom length						
Boom length  Operating temperature						
· ·	without accessories (Levixo 60)					
Operating temperature  Maximum number of operations/	without accessories (Levixo 60) -20° to +55°					
Operating temperature  Maximum number of operations/ day	without accessories (Levixo 60)  -20° to +55°  2000					

### Booms and fixation kits










## Length of boom

BOOM ACCESSORIES											
Rubber under boom (Ref. 9017045)				•	•	•		•	•	•	
Rubber over boom (Ref. 9017045)				•	•			•	•		
Led lighting kit (Ref. 9020718)				•				•			
Rest crutch (Ref. 9020720)				•	•	•	•				
LEVIXO 60	НЗ	L min	4.7 m	4.2 m	4.3 m	4.5 m	4.8 m	4.6 m	4.7 m	5 m	
		L max	6 m	5 m	5 m	5 m	5 m	5 m	5 m	5 m	
	H2	L min	4.1 m	2.6 m	3 m	3.2 m	3.4 m	3.3 m	3.4 m	3.6 m	
		L max	4.6 m	4 m	4.1 m	4.4 m	4.7 m	4.4 m	4.6 m	4.7 m	
LEVIXO 40	НЗ	L min	3.8 m	2.8 m							
		L max	4 m	4 m	4 m	4 m	4 m	4 m	4 m	4 m	
	H2	L min	2.9 m	2.2 m	2.3 m	2.5 m	2.6 m	2.6 m	2.6 m	2.6 m	
		L max	3.7 m	2.7 m							
	H1	L min	2.1 m	1.4 m	1.4 m	1.5 m	1.6 m	1.7 m	1.8 m	1.9 m	
		L max	3 m	2.2 m	2.3 m	2.5 m	2.6 m	2.6 m	2.7 m	2.7 m	



**Somfy** 50 avenue du Nouveau Monde 74300 CLUSES T +33 (0)4 50 96 70 00 F +33 (0)4 50 96 71 89 www.somfy.com

A BRAND OF **SOMFY** GROUP

Levixo 24V **BARRIER FOR VEHICLE** 



# Fast, intensive & reliable MADE FOR THE COLLECTIVE







### Somfy, your preferred partner

With more than 50 years by your side, Somfy is one of the top European leaders in the automatic control of openings and closures in homes and buildings. Because your comfort is our priority, our local teams is at your side supported by a R&D center in Europe.

# A dedicated range for your applications

Our barriers are suitable for both semi-intensive and intensive use, thanks to their motorisations in 230V and 24V. Our 3m and 5m rectangular booms and our 3m, 5m, and 6m rounded booms will adapt to your every need.



### LEVIXO 24V

# Benefit from all of its advantages



## An intensive use for the collective

- Up to 2000 openings/closings per day thanks to the 24V motor.
- Adjustable settings for collective needs such as courtesy light, pre signal or fast closing!
- Robust barrier and control board are compatible with various accessories such as orange light, led lights and rest crutch.



# The barrier to answer to all your needs

- Fast speed for an opening in 2,5 secondes.
- Compatible with rectangular or rounded boom up to 6 meters length.
- More than 40 settings adjustable including deceleration, acceleration, brake force and speed.
- Unlock with standard key to declutch the motor and protect the installation.
- Compatible with a timer and other accessories thanks to its two output contacts.



# o all A personnalised solution for all your installations!

- **Only one reference** of product for a left or right barrier.
- Easy installation thanks to its wide opening for cable passage, its removable door and internal space giving great freedom of movement during the installation.
- A robust barrier with a steel casing.

### READY TO DISCOVER THE SOMFY BARRIER OFFER?



